

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001733 A1

(51) International Patent Classification⁷: **G11B 7/24**

(21) International Application Number:
PCT/IB2003/002358

(22) International Filing Date: 4 June 2003 (04.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02077424.6 19 June 2002 (19.06.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PEETERS, Emiel** [NL/NL]; c/o Prof. Holstlaan 6, Eindhoven, 5656 AA

(NL). **BROER, Dirk, J.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **BUSCH, Christopher** [DE/NL]; c/o Prof. Holstlaan 6, Eindhoven, 5656 AA (NL).




(74) Agent: **DEGUELLE, Wilhelmus, H., G.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, Eindhoven, 5656 AA (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: MULTI-LAYER OPTICAL STORAGE USING PRE-ORIENTATION IN A GLASS MATRIX



(57) Abstract: The invention relates to producing an optical memory which combines stability of written and non-written data with high writing speed and good sensitivity during writing, such an optical memory as well as a method of writing in such a memory. The optical memory has a liquid crystal (LC) layer with a first type of LC molecules (102) aligned in one direction, forming a polymer network (108), and a second type of LC molecules (104) oriented in a perpendicular direction, in which the orientation of said second type of LC molecules is meta-stable. By making use of a force, exerted on the second type of LC molecules (104), by the network of aligned crosslinked molecules, an increase in relaxation rate for the second type of molecules (104) from a meta-stable state of orientation, is achieved, which makes it possible to use said relaxation for writing data at an increased writing rate.

WO 2004/001733 A1